



ENGINE DRIVEN
Gasoline

ENGINE HP	TANK CAP (GAL.)	GAS				NEW CAERSB MODEL DIMENSIONS			APPROX. WEIGHT LBS.	175 PSI RATING*			250 PSI RATING*		
		R-SERIES R2-30A	PUMP MODEL	PL-SERIES* CBEPLB	PUMP MODEL	L	W	H		RPM	CFM DISPL.	CFM DEL'Y	RPM	CFM DISPL.	CFM DEL'Y
13	NA	BGR7-H	R15B	BGPL7-H	PL15A	41.2	20.5	29.3	400	1025	29.9	23.2	950	27.7	19.8
13	(2) 4	HGR7-LPH	R15B	HGPL7-LPH	PL15A	41.3	22.3	37.6	500	1025	29.9	23.2	950	27.7	19.8
13	30	HGR7-3H	R15B	HGPL7-3H	PL15A	41.6	20.5	45.5	485	1025	29.9	23.2	950	27.7	19.8
13	60	HGR7-6H	R15B	HGPL7-6H	PL15A	52.5	21.3	49.1	585	1025	29.9	23.2	950	27.7	19.8
13	80	HGR7-8H	R15B	HGPL7-8H	PL15A	67.5	21.3	49.1	640	1025	29.9	23.2	950	27.7	19.8
14	NA	BGR7K	R15B	BGPL7K	PL15A	41.2	20.5	29.3	400	1025	29.9	23.2	950	27.7	19.8
14	(2) 4	HGR7-LPK	R15B	HGPL7-LPK	PL15A	41.3	22.3	37.6	500	1025	29.9	23.2	950	27.7	19.8
14	30	HGR7-3K	R15B	HGPL7-3K	PL15A	41.6	20.5	45.5	485	1025	29.9	23.2	950	27.7	19.8
14	60	HGR7-6K	R15B	HGPL7-6K	PL15A	52.5	21.3	49.1	585	1025	29.9	23.2	950	27.7	19.8
14	80	HGR7-8K	R15B	HGPL7-8K	PL15A	67.5	21.3	49.1	640	1025	29.9	23.2	950	27.7	19.8
20.5	NA	BGR10K	R30D	BGPL10K	PL30A	34	23	29	540	765	44.6	36.2	680	39.6	31.2
22.5	5	BGR12K	R30D	BGPL12K	PL30A	46	28	35.8	590	940	55	44.2	810	47.2	38.4

H - Honda. K - Kohler. NOTES: *Only pressure lubricated units are capable of 250 PSIG operation. Units tested in accordance with CAGI/PNEUROP Acceptance Test Code PN2CPTC3. Dimensions are for R-Series compressors. Add 1" to the width for PL units.

COMPRESSOR/GENERATOR

ENGINE HP	TANK CAP (GAL.)	GAS			HGRV7-LPH-G DIMENSIONS			APPROX. WEIGHT LBS.	175 PSI RATING		
		COMP/GEN MODEL	COMP/GEN PART NUMBER	PUMP MODEL	L	W	H		RPM	CFM DISPL.	CFM DEL'Y
13	(2) 4	HGRV7-LPH-G	CC1153480	RV15A	46	22	35	490	784	22.9	17.9



KOHLER
14 HP
Command Pro
CH440



KOHLER
20 HP
Command Pro
CH640



KOHLER
23 HP
Command Pro
CH680



HONDA
13 HP
GX390



ENGINE DRIVEN
Diesel

ENGINE HP	TANK CAP GAL.	DIESEL				NEW CAERSB MODEL DIMENSIONS			APPROX. WEIGHT LBS.	175 PSI RATING*			250 PSI RATING*		
		R-SERIES R2-30A	PUMP MODEL	PL-SERIES* CBEPLB	PUMP MODEL	L	W	H		RPM	CFM DISPL.	CFM DEL'Y	RPM	CFM DISPL.	CFM DEL'Y
9.1	NA	BDR5K	R15B	BDPL5K	PL15A	41.2	20.6	29.3	440	870	25.3	20.1	650	18.9	13.6
9.1	30	HDR5-3K	R15B	HDPL5-3K	PL15A	41.6	20.5	45.5	570	870	25.3	20.1	650	18.9	13.6
9.1	80	HDR5-8K	R15B	HDPL5-8K	PL15A	67.5	21.3	49.1	680	870	25.3	20.1	650	18.9	13.6
9.1	NA	BDR5Y	R15B	BDPL5Y	PL15A	41.2	20.6	29.3	440	940	27.4	21.7	810	23.6	18.7
9.1	30	HDR5-3Y	R15B	HDPL5-3Y	PL15A	42.7	20.5	45.5	570	940	27.4	21.7	810	23.6	18.7
9.1	80	HDR5-8Y	R15B	HDPL5-8Y	PL15A	67.5	21.3	49.1	680	940	27.4	21.7	810	23.6	18.7

K - Kohler, Y-Yanmar.

NOTE: Only pressure lubricated units are capable of 250 PSIG operation.
Units tested in accordance with CAGI/PNEUROP Acceptance Test Code PN2CPTC3.
Dimensions are for R-Series compressors. Add 1" to the width for PL units.



KOHLER
9.1 HP
Kohler Diesel
KD-440



YANMAR
9.1 HP
L100V

