

MEDICAL | 5 HP ROTARY SCROLL AIR COMPRESSORS

CA-Series S5

The CA-Series compressors provide the reliable, high quality compressed air that you've come to expect from Champion. Designed specifically for medical applications that require 100% oil-less air, NFPA 99 and CSA compliance. CA-Series compressors offer a wide selection of configurations and top-quality available options. No matter the application, Champion gets the job done.

Standard Equipment

- Continuous operation, 100% duty cycle
- Mounted control panel
- MediTrol: duplex
- MediTrol Plus HMI: triplex, quad
- Vinyl lined receiver
- Extremely low noise and vibration
- Premium efficient TEFC motor
- ASME pressure relief valve
- Air-cooled aftercooler with separator and trap
- Remote inlet filter
- Receiver sight and pressure gauges

Available Options

- Galvanized receiver
- Remote tank available in 80, 120 or 240 gallon
- Medical desiccant dryer system with dew point and CO monitoring
- MediTrol Plus HMI control panel (duplex)



BARE AIREND

MODEL	DIMENSIONS L × W × H IN.	APPROX. SHIP WEIGHT LBS		
SC5	13.6 × 14.7 × 11.4	45		

DUPLEX

MOTOD UD	BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L × W × H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
MOTOR HP					RPM	ICFM	RPM	ICFM
5	Base	BCAS5D-M	72 × 48 × 43.5	1124	3100	14.1	2900	12.7
5	80	HCAS5D-8-M	65 × 34 × 61.5	1400	3100	14.1	2900	12.7
5	120	HCAS5D-12-M	69 × 34 × 65.5	1500	3100	14.1	2900	12.7
5	240	HCAS5D-24-M	86 × 40 × 71.5	1700	3100	14.1	2900	12.7

Duplex units have two motors and two pumps on one base/tank. Performance based on full system operation with one compressor in reserve per NFPA 99.

TRIPLEX

MOTOR HP	BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L × W × H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
					RPM	ICFM	RPM	ICFM
5	Base with 80 Remote	BCAS5T-M	129 × 48 × 69	2238	3100	28.2	2900	25.4

Triplex units have three airends and three motors stacked on a common base. Performance based on full system operation with one compressor in reserve per NFPA 99. Optional larger 120 or 240 gallon remote tanks available.

QUADRAPLEX

	MOTOR HP		IDENTIFICATION		APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
			NUMBER			RPM	ICFM	RPM	ICFM
	5	Base with 80 Remote	BCAS5Q-M	129 × 48 × 69	3011	3100	42.3	2900	38.1

Quadraplex units have four airends and four motors stacked on a common base. Performance based on full system operation with one compressor in reserve per NFPA 99. Optional larger 120 or 240 gallon remote tanks available.



1301 North Euclid Avenue Princeton, Illinois 61356 USA 866-276-4330 www.ChampionPneumatic.com

©2017 Gardner Denver, Inc. Printed in U.S.A. CLCS-CA-MED-S5 3rd Ed. 2/17



Please recycle after use.

